

**Expedited Procedure Under 37 CFR §1.116**

Application No. 10/587,741

Paper Dated: October 27, 2010

In Reply to USPTO Correspondence of July 27, 2010

Attorney Docket No. 5503-061852

**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims**

Claims 1-26 have been cancelled.

27. (Currently Amended) A method for operating a refrigeration plant, which comprises in a refrigeration circuit a compressor (5), a condenser, an injection valve (6) with an entrance and an exit, and an evaporator (1), the evaporator which is being passed through on its secondary side by a secondary medium to be cooled down, whereby a heat exchanger (4) is provided between a feed line for the secondary medium and a refrigerant line leading to the entrance of said injection valve (6), and whereby the method is comprised of the step of keeping constant the temperature (A) of the refrigerant at the entrance of the injection valve (6) ~~is kept constant~~, thereby achieving a stable operation of and hence a highly efficient evaporation in the refrigeration circuit.

28. (Currently Amended) The method according to claim 27, further including the step of at least partially passing wherein the a mass flow of the cooled-down secondary medium ~~is at least partly passed through~~ the heat exchanger (4) in ~~a~~ parallel or counter-flow or cross-flow with respect to the refrigerant flow by means of a first valve (11).

29. (Currently Amended) A method according to claim 27, further including the step of passing whereby the refrigerant leaving said evaporator (1) ~~is passed~~ through an internal heat exchanger (2), which may operate as a second evaporating means.

30. (Currently Amended) A method according to claim 29, whereby, by means of a second valve (9) provided between said refrigerant line leading to said injection valve (6) and said internal heat exchanger (2), further including the step of passing a predetermined

**Expedited Procedure Under 37 CFR §1.116**

Application No. 10/587,741

Paper Dated: October 27, 2010

In Reply to USPTO Correspondence of July 27, 2010

Attorney Docket No. 5503-061852

part of the refrigerant mass flow ~~is passed~~ through said internal heat exchanger (2), while the remaining mass flow is directly conducted to said injection valve (6), to additionally keep the temperature (A) of the refrigerant at the entrance of the injection valve (6) constant.

31. (Currently Amended) A refrigeration plant for conducting the method according to one of the claims 27-30, whereby said refrigeration plant comprises in a refrigeration circuit a compressor (5), a condenser, an injection valve (6) with an entrance and an exit and an evaporator (1), ~~which is~~ wherein the evaporator being passed through on its secondary side by a secondary medium to be cooled down, whereby a heat exchanger (4) is provided between a feed line for the secondary medium and a refrigerant line leading to the entrance of said injection valve (6), ~~which~~ wherein the heat exchanger is passed through by said refrigerant ~~on its~~ the primary side of the heat exchanger, and by said cooled-down secondary medium ~~on its~~ the secondary side of the heat exchanger.

32. (Currently Amended) Refrigeration plant according to claim 31, whereby a first valve (11) is arranged at the secondary side of said heat exchanger (4), such that ~~the~~ a mass flow of said cooled-down secondary medium is at least partly passed through said heat exchanger in a parallel or counter-flow or cross-flow with respect to the refrigerant flow.

33. (Previously Presented) Refrigeration plant according to claim 31, whereby the refrigerant leaving said evaporator (1) is passed through an internal heat exchanger (2), and whereby a second valve (9) is provided between said refrigerant line leading to said injection valve (6) and said internal heat exchanger (2), such that a predetermined part of the refrigerant mass flow is passed through said internal heat exchanger (2), while the remaining mass flow is directly conducted to said injection valve (6).